



## MATERIAL SAFETY DATA SHEET

### 1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

#### Identification of substance / preparation

PRODUCT : EURO GULF MOTOR OIL SAE 5W40

PERFORMANCE LEVEL : API SN

CHEM FAMILY : PETROLEUM HYDROCARBON

HEALTH HAZARD : NON-HAZARDOUS SUBSTANCE, NON-DANGEROUS GOODS.

#### Application

AUTOMOTIVE ENGINE LUBRICANT

For specific application advice see appropriate Technical Data Sheet.

#### Company Identification

SAMER AL GADDAH INTERNATIONAL GENERAL TRADING CO. LLC.

### 2. COMPOSITION

SUBSTANCE NAME	FORM	CAS NO.	CONCENTRATION
DISTILATE HEAVY HYDROTREATED PARAFFINIC (HYDROCARBONS)	LIQUID	64742-54-7	80 – 90%
ADDITIVE	LIQUID	MIXTURE	10 -20%

### 3. HAZARDS IDENTIFICATION

This material is not considered to be hazardous, but should be handled in accordance with good industrial hygiene and safety practices.

### 4. FIRST-AID MEASURES

#### Eyes

Wash eye thoroughly with copious quantities of water, ensuring eyelids are held open. Obtain medical advice if any pain or redness develops or persists.

#### Skin

Wash skin thoroughly with soap and water as soon as reasonably practicable. Remove heavily contaminated clothing and wash underlying skin.



### **Ingestion**

If contamination of the mouth occurs, wash out thoroughly with water. Except as a deliberate act, the ingestion of large amounts of product is unlikely. If it should occur, do not induce vomiting; obtain medical advice.

### **Inhalation**

If inhalation of mists, fumes or vapor causes irritation to the nose or throat, or coughing, remove to fresh air. If symptoms persist obtain medical advice.

### **Medical Advice**

Treatment should in general be symptomatic and directed to relieving any effects.

## **5. FIRE-FIGHTING MEASURES**

Use foam, dry powder or water fog. DO NOT USE water jets.

Fires in confined spaces should be dealt with by trained personnel wearing approved breathing apparatus.

Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over.

### **Combustion Products**

Toxic fumes may be evolved on burning or exposure to heat.

See Stability and Reactivity, Section 10 of this Safety Data Sheet.

## **6. ACCIDENTAL RELEASE MEASURES**

Contain and recover spilled material using sand or other suitable inert absorbent material.

It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated.

Spilled material may make surfaces slippery.

Protect drains from potential spills to minimize contamination. Do not wash product into drainage system.

In the case of large spills contact the appropriate authorities.

In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies

## **7. HANDLING AND STORAGE**

Handling Precautions Avoid contact with eyes. If splashing is likely to occur wear a full-face visor or chemical goggles as appropriate. Avoid frequent or prolonged skin contact with fresh or used product. Good working practices, high standards of personal hygiene and plant cleanliness must be maintained at all times. Wash hands thoroughly after contact.

Use disposable cloths and discard when soiled. Do not put soiled cloths into pockets.



#### Storage Conditions

Store under cover away from heat and sources of ignition.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Exposure Limits

There is no appropriate occupational exposure limit for this material.

Ensure good ventilation.

Avoid, as far as reasonably practicable, inhalation of vapor, mists or fumes generated during use.

If vapor, mists or fumes are generated, their concentration in the workplace air should be controlled to the lowest reasonably practicable level.

#### Protective Clothing

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

If skin contact is likely, wear impervious protective clothing and/or gloves.

Protective clothing should be regularly dry cleaned. Change heavily contaminated clothing as soon as reasonably practicable; dry clean, launder and preferably starch before re-use. Wash any contaminated underlying skin with soap and water.

#### Respiratory Protection

Respiratory protection is unnecessary, provided the concentration of vapor, mists or fumes is adequately controlled.

The use of respiratory equipment must be strictly in accordance with the manufacturers' instructions and any statutory requirements governing its selection and use.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

TESTS	METHOD	RESULTS
Appearance	VISUAL	Bright & Clear
Odor	-	Characteristic of hydrocarbons.
DENSITY @ 15°C, g/cm <sup>3</sup>	ASTM D1298	0.8503
VISCOSITY @ 40°C, cSt	ASTM D445	96.56
VISCOSITY @ 100°C, cSt	ASTM D445	13.91
VISCOSITY INDEX	ASTM D2270	147
FLASH POINT, °C	ASTM D92	231
POUR POINT, °C	ASTM D97	-36
TBN VALUE	ASTM D2896	7.2



## 10. STABILITY AND REACTIVITY

Products of this type are stable and unlikely to react in a hazardous manner under normal conditions of use. Hazardous polymerization reactions will not occur.

This material is combustible.

### Materials to Avoid

Avoid contact with strong oxidizing agents.

### Hazardous Decomposition Products

Thermal decomposition products will vary with conditions.

Incomplete combustion will generate smoke, carbon dioxide and hazardous gases, including carbon monoxide, hydrogen sulfide and oxides of sulfur and phosphorus.

## 11. TOXICOLOGICAL INFORMATION

### Eyes

Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.

### Skin

Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis.

## 12. DISPOSAL CONSIDERATIONS

Where possible, arrange for product to be recycled.

Dispose of via an authorized person/ licensed waste disposal contractor in accordance with local regulations.

Incineration may be carried out under controlled conditions provided that local regulations for emissions are met.

## 13. ECOLOGICAL INFORMATION

### Mobility

Spillages may penetrate the soil causing ground water contamination.

### Persistence and degradability

This product is inherently biodegradable.

### Bio accumulative potential

There is no evidence to suggest bioaccumulation will occur.



### **Aquatic toxicity**

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

### **14. TRANSPORT INFORMATION**

Not classified as hazardous for transport (ADR, RID, UN, IMO, and IATA/ICAO).

### **15. REGULATORY INFORMATION**

Not classified as hazardous for supply. This data sheet and the health, safety and environmental information it contains is considered to be accurate as of the date specified below. We have reviewed any information contained herein which we received from sources outside of Company. However, no warranty or representation, express or implied is made as to the accuracy or completeness of the data and information contained in this data sheet.

Risk phrase(s): None

Safety phrase(s): None

EU directives: Hazardous preparations directive 1999/45/EC modified (Directive 2001/60/EC)

### **16. OTHER INFORMATION**

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license. The company shall not be responsible for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.